

Package Contents:

Socket 4 x 1

Socket 6 x 1

green light 15CM x 1

Warm light headlight 30CM x 3

Color light strip A warm light (3 sections) x 1

Color light strip B warm light (1 section) x 1

Cable 30CM x 1

Battery box AA (USB port) x 1

USB port 50CM x 1


Some building blocks

Notes (the pictures in this paragraph are for demonstration purposes only and are not parts of this set):

Routing above and below the board

Wires can be run between boards or underneath boards , but they must be placed correctly between studs.






Connect the electrical outlet to the socket


Be extremely careful when inserting the wire plug into the outlet. The plug only goes in one way. With the plug facing up, look for the soldered "=" symbol on the left side of the port. The side of the plug with the exposed wires should be facing the soldered "=" symbol as you insert it into the port. If the plug does not fit easily into the port, do not force it.


Inserting the socket incorrectly may cause the pins inside the port to bend or may cause the socket to overheat when connected.






When installing the light pellets on the building blocks , make sure they are properly positioned (with the yellow LED assembly exposed). You can place them directly on top of the building block studs or in between.











Insert the battery into the battery compartment

The specifications of several battery boxes are different, please pay attention to the positive and negative poles of the batteries.

AA battery box Correct battery installation



Button battery box (flat) battery correct installation method



Button battery box (round) battery correct installation



Installation Instructions


Take out the AA battery box and correctly install 3 AA batteries (new batteries are recommended)



Remove the USB power cable and insert it into the battery box




Take a 6-socket and plug the power cord into the 6-socket




Plug and socket connection method


Align the "=" on the plug with the "=" side on the receptacle



The "=" on the plug
can clearly see one
side of the line



There are two silver
dots next to the "="
socket on the socket



equal sign equal sign



Take a 30cm warm light headlight and insert it into 6 seats



LYBMTWF

Turn on the power and test that the light is on normally



After the test, turn off the power, pull out the lamp, and leave the 6 lamps on the power supply.



Take out the building



LYBMTWF

Dismantling the red telephone booth



LYBMTWF

Remove the parts indicated by arrows one by one



LYBMTWF





LYBMTWF




LYBMTWF

Continue to decompose the parts shown in the figure one by one





LYBMTWF




LYBMTWF


Take 1 30cm warm light headlight pellet, 1 1x2 transparent piece



the light particle with the luminous side facing downward in the center of the transparent piece, and fit the wire to the arc.




Install 1x2 transparent parts to fix the light particles



LYBMTWF

Pass the wire through the gap as shown in the figure



LYBMTWF

Restore transparent parts



LYBMTWF




Restore gray parts




LYBMTWF

Go to the back side, fit the wire to the angle, and pass it over the raised part.




LYBMTWF

Restore the green parts and fix the wires



Restore the parts as a whole, with the wires on the back (note the direction of the telephone booth)




Go to the back of the phone booth



LYBMTWF

Remove the parts indicated by arrows one by one





LYBMTWF

Fit the wire to the angle and pass through the gaps between the raised particles.



LYBMTWF



The effect after sorting is as follows



Restore parts and fix wires



Continue to pass the wire along the part angle



Restore parts and fix wires



Remove the parts indicated by the arrows.




LYBMTWF

Pass the wire along the gaps between the raised particles




LYBMTWF

Restore parts and fix wires




LYBMTWF


Take out the light strip A and prepare to install it on the roof




Tear off the adhesive backing of the headlight strip




Paste the light strip to the position shown in the figure, and the remaining light strip is on the top (pay attention to the direction of the roof , refer to the position shown by the blue circle)



Continue to stick the remaining light strips to the edge of the roof, with the tail wire at the bottom.




Fit the wires between the light strips to the parts



Restore the roof, the tail wire is on the back of the phone booth



Remove the parts indicated by the arrows.



LYBMTWF

Pass the tail wire downward around the raised particles.




Restore parts and fix tail wires




LYBMTWF


Take out the light strip B



Place the phone booth on its side, pay attention to the direction, the tail line
is on the left




Paste the light strip to the position shown in the figure



LYBMTWF

Continue to stick the light strips to the edge of the base.




Turn the phone booth back to the original position .




LYBMTWF

Remove the parts indicated by the arrows.




LYBMTWF

Pull the tail of the light strip along the gap between the raised particles and pull
it upwards



Restore parts and fix tail wires




the telephone booth aside



LYBMTWF

Take out the base and remove the parts indicated by the arrows one by one.






LYBMTWF




LYBMTWF

Decompose the flowers as follows




Take 1 15cm green light pellet, 2 hollow transparent round




LYBMTWF

Bend the lamp 90° with the light-emitting side facing outwards



Put the lamp plug through the small hole in the hollow circle.




LYBMTWF

Tighten the wire so that the light-emitting side of the lamp faces outward and fits onto the protrusion.



LYBMTWF

Install the hollow transparent circle to fix the light particles




Install the lamp to the center of the part, paying attention to the direction of
the part




LYBMTWF

Continue to pass the wire through the gap in the part.




LYBMTWF

From below, the effect is as follows




Restore the part, with the wire on the left



Restore the flowers above




Remove the white card




LYBMTWF

Decompose the brand as follows, take 1 30cm warm light headlight pellet




LYBMTWF

Place the light pellet with the luminous side facing downwards and fit it to the position shown in the picture. Pay attention to the direction of the white card.




LYBMTWF

Hold the lamp and place the wire on the back of the white card.




Restore parts and fix wires




LYBMTWF


Route the wires around the grey parts




Restore the white card, the wire is on the left




Pass the wire through the gap in the fence to the back




Tighten the wires from the back



Remove the parts indicated by the arrows.




Pass the wire through the gap under the fence




LYBMTWF

With the help of a lifter , the wire is passed through the gaps between the raised particles.




LYBMTWF


Restore parts and fix wires



Continue to fit the wire to the part angle and pass through the gaps between the raised particles.




The effect after sorting is as follows




Restore parts and fix wires




Turn to the side and remove the parts indicated by the arrow





LYBMTWF


Fit the wire to the edge of the part through



Restore parts and fix wires




Remove the parts indicated by the arrows.




LYBMTWF

Fit the wire to the edge of the part through




Restore parts and fix wires




LYBMTWF

Bring the two wires together and fit them along the edge of the part.



Restore parts and fix wires




Adjust the position of the light particles so that they can illuminate the bottom




Take a 30cm warm light headlight and prepare to install it on the street light




Decompose the street lights one by one





LYBMTWF

the lamp wires by 1 gap



LYBMTWF


Put the light pellets with the luminous side facing upwards and put them on the orange parts.




LYBMTWF

 Hi Brick

Tighten the wires appropriately to fix the lamp particles



Restore transparent cover




LYBMTWF

Route the wires through the bracket




LYBMTWF

Separate a gap under the lamp post



LYBMTWF

Pass the wire through the gap



LYBMTWF

Restore the gap and fix the wire



LYBMTWF


Restore the street light, with the wire on the left, and pay attention to the direction
of the street light



Restore black parts




Take a 4-seat and a 30cm connecting wire, and insert the connecting wire into the
4-seat side socket




LYBMTWF

Insert all 3 wires into the 4 sockets



LYBMTWF

Plug the connecting wire on the 4th socket into the 6th socket connected to the power supply




LYBMTWF

Turn on the power and test that the light is on normally



LYBMTWF

After the test, turn off the power, unplug the connection cable, and leave the 6 sockets on the power supply.




LYBMTWF

Tear off the adhesive backing of the 4 seats




LYBMTWF

Paste the 4 seats to the positions shown in the figure




LYBMTWF

Pass the connecting line along the gaps between the raised particles



LYBMTWF

Restore the gray tablet and fix the connection line




LYBMTWF

Twist the excess wires together and stuff them into the gap.




LYBMTWF

Use a tool to pry open a gap in the part as shown in the picture.




LYBMTWF

Pull the connecting line along the gap to the back



LYBMTWF

Restore the gap and fix the connection line




Go to the back of the base




LYBMTWF


Remove the left fence



Remove the plate indicated by the arrow.




Pass the connection line along the part angle



LYBMTWF

Restore parts and fix connecting wires




LYBMTWF

Restoring the Phone Booth



LYBMTWF

Insert all 4 wires into the 6 sockets




LYBMTWF


Turn on the power, test that the light is on normally, and turn off the power after the test is completed.




Paste the 6 seats to the position shown in the figure



Tuck the extra wires into the gap (except the USB cable)



Restore Fence




LYBMTWF

Go to the side




LYBMTWF

Remove the gray plate indicated by the arrow.



LYBMTWF

Use the tablet to fix the USB cable



At this point, the installation of this set of lighting is complete. Turn on the power and enjoy it!



If you want the light to stay on, plug the USB port into a USB power source.

